

## POWERMOUNT UNI

### GPM.UNI

Transparent polyester film coated double sides adhesive film. The pressure sensitive adhesive is solvent-free, environment friendly. Permanent adhesive for the mounting of a wide variety of substrates. Excellent processing characteristics, providing excellent adhesion to a wide variety materials like photo, inkjet print, plastics, films, wood, glass, aluminium and other metals. Suitable for indoor and outdoor applications.

#### FEATURES

12µm transparent polyester film  
Double-sides coated adhesive, polyacrylate, solvent-free, pH-neutral, age resistant  
The adhesive provides excellent adhesion to various substrates.  
Double sides siliconized release paper  
Durability up to 2 years

#### PHYSICAL PROPERTIES

Carrier	Transparent polyester film, 12µm
Total Thickness	70 µm
Surface	Mount
Adhesive	Solvent free, polyacrylate, permanent
Liner	Double sides siliconized paper, white, 90 g/m <sup>2</sup>
Peel adhesion	11 (AFERA 5001)

#### ENVIRONMENTAL CONDITIONS

Operating	8°-40°C
Storage	18°-22°C (50-60% rH non condensing)

#### AVAILABLE SIZES

65 cm x 50 m  
104 cm x 50 m  
140 cm x 50 m  
155 cm x 50 m

#### ADDITIONAL INFORMATION

The estimated durability is based on accelerated ageing tests and refers to a vertical exposure under middle European climates. The durability of the product depends on the substrate's preparation, the atmospheric conditions and the environmental influence. Exposure to extreme condition (tropical climate, desert climate, high humidity, high UV-light exposure or polluted areas) may cause rapid deterioration.

Please include always the batch number to questions about the product or complaints.  
(see inside sleeve)

Specifications subject to change without notice.  
All trademarks are the property of their respective companies.